## NSN 5945-00-201-7534

Thermal Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-201-7534

v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Overall Height: 4.219 inches Overall Width: 4.500 inches Environmental Protection: Fire resistant Contact Arrangement: Single pole, single throw, normally closed Mounting Facility Type And Quantity: 3 unthreaded hole Contact Maximum Voltage Rating In Volts: 550.0 ac Contact Maximum Current Rating In Amps: 20.0 ac Special Features: Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:	Overall Length:
4.219 inches  Overall Width: 4.500 inches  Environmental Protection:  Fire resistant  Contact Arrangement:  Single pole, single throw, normally closed  Mounting Facility Type And Quantity: 3 unthreaded hole  Contact Maximum Voltage Rating In Volts: 550.0 ac  Contact Maximum Current Rating In Amps: 20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, nor rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Sheeft Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	5.438 inches
Overall Width: 4.500 inches  Environmental Protection: Fire resistant  Contact Arrangement: Single pole, single throw, normally closed  Mounting Facility Type And Quantity: 3 unthreaded hole  Contact Maximum Voltage Rating In Volts: 550.0 ac  Contact Maximum Current Rating In Amps: 20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: No  Fig:	Overall Height:
4.500 inches  Environmental Protection: Fire resistant  Contact Arrangement: Single pole, single throw, normally closed  Mounting Facility Type And Quantity: 3 unthreaded hole  Contact Maximum Voltage Rating In Volts: 550.0 ac  Contact Maximum Current Rating In Amps: 20.0 ac  Special Features: Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	4.219 inches
Environmental Protection: Fire resistant  Contact Arrangement: Single pole, single throw, normally closed  Mounting Facility Type And Quantity: 3 unthreaded hole  Contact Maximum Voltage Rating In Volts: 550.0 ac  Contact Maximum Current Rating In Amps: 20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, waitage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Overall Width:
Fire resistant  Contact Arrangement:  Single pole, single throw, normally closed  Mounting Facility Type And Quantity:  3 unthreaded hole  Contact Maximum Voltage Rating In Volts:  550.0 ac  Contact Maximum Current Rating In Amps:  20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	4.500 inches
Contact Arrangement:  Single pole, single throw, normally closed  Mounting Facility Type And Quantity:  3 unthreaded hole  Contact Maximum Voltage Rating In Volts:  550.0 ac  Contact Maximum Current Rating In Amps:  20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Environmental Protection:
Single pole, single throw, normally closed  Mounting Facility Type And Quantity:  3 unthreaded hole  Contact Maximum Voltage Rating In Volts:  550.0 ac  Contact Maximum Current Rating In Amps:  20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Fire resistant
Mounting Facility Type And Quantity:  3 unthreaded hole  Contact Maximum Voltage Rating In Volts:  550.0 ac  Contact Maximum Current Rating In Amps:  20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Contact Arrangement:
3 unthreaded hole  Contact Maximum Voltage Rating In Volts:  550.0 ac  Contact Maximum Current Rating In Amps: 20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  No  Fig:	Single pole, single throw, normally closed
Contact Maximum Voltage Rating In Volts:  550.0 ac  Contact Maximum Current Rating In Amps:  20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Mounting Facility Type And Quantity:
Contact Maximum Current Rating In Amps:  20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	3 unthreaded hole
Contact Maximum Current Rating In Amps:  20.0 ac  Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Contact Maximum Voltage Rating In Volts:
Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	550.0 ac
Special Features:  Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Contact Maximum Current Rating In Amps:
Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, a v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	20.0 ac
v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Special Features:
ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Contact data, electrical ratings, 4amp nom current rating, 110 v at maximum rated current, w at maximum current not rated; heater data, ac,
sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no terminals, for general purpose use  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	v, not rated, wattage not rated, 6.85 amp; terminal data 2 heater element terminals, 2 terminals for contacts; plastic case; not rated for
terminals, for general purpose use  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	ambient temp range compensation; rated for acutation time, 900 sec at 125 pct of continuous load, 175 sec at 200 pct of continuous load, 72
Shelf Life:  N/a Unit Of Measure: Demilitarization: No Fiig:	sec at 300 pct of continuous load operating time; special features, long reset rod, adjustable 90 to 110 pct of rating, coil w/10 in. Leads, no
N/a Unit Of Measure: Demilitarization: No Fiig:	terminals, for general purpose use
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A 50010	Fiig:
A50010	A500I0