## NSN 5945-00-204-8138

Electromagnetic Relay - Page 1 of 2

Unc single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-204-8138

Thread Class:  2a single mounting facility  Overall Length:  1.840 inches  Overall Height:  2.060 inches  Overall Width:  1.400 inches  Environmental Protection:  Watertight  End Application:  Type c-1600/spa  Frequency In Hertz:  60.0  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:  400.0 ohms single winding and 1.4 kilohms single winding
Overall Length:  1.840 inches  Overall Height:  2.060 inches  Overall Width:  1.400 inches  Environmental Protection:  Watertight  End Application:  Type c-1600/spa  Frequency In Hertz:  60.0  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:
1.840 inches Overall Height: 2.060 inches Overall Width: 1.400 inches Environmental Protection: Watertight End Application: Type c-1600/spa Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating:
Overall Height: 2.060 inches  Overall Width: 1.400 inches  Environmental Protection:  Watertight  End Application:  Type c-1600/spa  Frequency In Hertz: 60.0  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating:
2.060 inches  Overall Width:  1.400 inches  Environmental Protection:  Watertight  End Application:  Type c-1600/spa  Frequency In Hertz:  60.0  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:
Overall Width:  1.400 inches  Environmental Protection:  Watertight  End Application:  Type c-1600/spa  Frequency In Hertz:  60.0  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:
1.400 inches  Environmental Protection:  Watertight  End Application:  Type c-1600/spa  Frequency In Hertz:  60.0  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:
Environmental Protection:  Watertight End Application: Type c-1600/spa Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating:
Watertight  End Application: Type c-1600/spa  Frequency In Hertz: 60.0  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating:
End Application:  Type c-1600/spa  Frequency In Hertz: 60.0  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating:
Type c-1600/spa  Frequency In Hertz: 60.0  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating:
Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating:
Winding Quantity:  Coil Quantity:  Winding Dc Resistance Rating:
Winding Quantity:  Coil Quantity:  Winding Dc Resistance Rating:
Coil Quantity:  Winding Dc Resistance Rating:
Coil Quantity:  1 Winding Dc Resistance Rating:
1 Winding Dc Resistance Rating:
Winding Dc Resistance Rating:
400.0 ohms single winding and 1.4 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Pile-up Main Contact Form Arrangement:
2a
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.812 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac
Thread Series Designator:

## NSN 5945-00-204-8138

Electromagnetic Relay - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

6 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300