# NSN 5945-00-205-9416

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-205-9416

### **Overall Length:**

1.750 inches

#### **Overall Height:**

1.500 inches

## **Overall Width:**

0.625 inches

#### **Environmental Protection:**

Hermetic and shock resistant and vibration resistant

#### **Fragility Factor:**

Moderately rugged

#### Winding Quantity:

1

#### Purpose For Which Designed:

General

**Coil Quantity:** 

1

#### Winding Dc Resistance Rating:

270.0 ohms single winding and 330.0 ohms single winding

**Duty Type:** 

Continuous

### Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

#### Storage Type:

General purpose warehouse

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

0.015 seconds fixed operate and release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

800.0 milliamperes ac lamp load and 1.0 amperes dc lamp load

## Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

8 pin all functions

## Specification Data:

81349-mil-r-5757/23 government specification

# NSN 5945-00-205-9416

Electromagnetic Relay - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

