# NSN 5945-00-209-4987

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-209-4987

## **Overall Length:**

4.520 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.880 inches single mounting facility

## **Overall Height:**

3.090 inches

Overall Width:

3.250 inches

Case Material:

Metal

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.199 inches single mounting facility

#### Fragility Factor:

Moderately rugged

Winding Quantity:

1

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

#### **Duty Type:**

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

**Cubic Measure:** 

45.392 cubic inches

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

0.10 seconds adjustable release time and 1.00 seconds adjustable release time

## Operating Voltage Rating And Type At Specificationified Temp:

125.0 volts dc 25 degrees celsius single winding

## NSN 5945-00-209-4987

Electromagnetic Relay - Page 2 of 2



#### Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

## Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300