# NSN 5945-00-214-5750

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-214-5750

# Overall Length:

1.666 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.390 inches single mounting facility

# **Overall Height:**

1.510 inches

#### **Overall Width:**

1.000 inches

#### Mounting Slot Width:

0.150 inches single mounting facility

#### Case Material:

Metal

**Environmental Protection:** 

Hermetic

#### Fragility Factor:

Moderately rugged

### Contact Material:

Silver

### **Contact Surface Treatment:**

Gold

### Winding Quantity:

1

### **Purpose For Which Designed:**

General

### **Coil Quantity:**

1

### Winding Dc Resistance Rating:

150.0 ohms single winding

Duty Type:

Continuous

### Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

2.515 cubic inches

#### Mounting Facility Pattern:

In-line single mounting facility

#### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

## **Operating Current Rating And Type:**

80.0 milliamperes dc single winding

# NSN 5945-00-214-5750

Electromagnetic Relay - Page 2 of 2



**Time Delay:** 0.007 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Silver and gold **Terminal Type And Quantity:** 14 pin all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300