NSN 5945-00-224-5002

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-224-5002

| Overall Length: |
|---|
| 1.180 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.124 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.000 inches single mounting facility |
| Overall Height: |
| 0.400 inches |
| Overall Width: |
| 1.085 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.096 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 1.025 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Features Provided: |
| Polarized |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.5 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 100.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5945-00-224-5002

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300