

View Online at <https://aerobasegroup.com/nsn/5945-00-225-1987>

**Thread Class:**

2a power takeoff facility stud

**Body Style:**

Enclosed frame

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.680 inches

**Mounting Slot Width:**

Between 0.186 inches and 0.201 inches

**Body Length:**

2.950 inches

**Body Width:**

1.000 inches

**Body Height:**

1.110 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Duty Type:**

Intermittent

**Terminal Location:**

End opposite actuator

**Voltage Rating In Volts:**

24.0 dc

**Mounting Facility Type And Quantity:**

3 slot

**Current Rating:**

8.0 amperes

**Thready Qty Per Inch (tpi):**

28 power takeoff facility stud

**Actuator Stroke Type:**

Pull

**Linear Force Delivered:**

9.00 pounds

**Power Takeoff Connection Type:**

External threads

**Thread Size:**

0.250 inches power takeoff facility stud

**Mounting Facility Pattern:**

Isosceles triangle

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

2.330 inches

**Thread Series Designator:**

Unf power takeoff facility stud

**Terminal Type And Quantity:**

2 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiiig:**

A134a0