

View Online at <https://aerobasegroup.com/nsn/5945-00-225-1987>

Thread Class:

2a power takeoff facility stud

Body Style:

Enclosed frame

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.680 inches

Mounting Slot Width:

Between 0.186 inches and 0.201 inches

Body Length:

2.950 inches

Body Width:

1.000 inches

Body Height:

1.110 inches

Environmental Protection:

Shock resistant and vibration resistant

Inclosure Type:

Fully enclosed

Magnetic Coil Quantity:

1

Duty Type:

Intermittent

Terminal Location:

End opposite actuator

Voltage Rating In Volts:

24.0 dc

Mounting Facility Type And Quantity:

3 slot

Current Rating:

8.0 amperes

Thready Qty Per Inch (tpi):

28 power takeoff facility stud

Actuator Stroke Type:

Pull

Linear Force Delivered:

9.00 pounds

Power Takeoff Connection Type:

External threads

Thread Size:

0.250 inches power takeoff facility stud

Mounting Facility Pattern:

Isosceles triangle

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.330 inches

Thread Series Designator:

Unf power takeoff facility stud

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A134a0