## NSN 5945-00-226-0131

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-226-0131

Terminal Quantity:
5
Terminal Type:
Threaded stud
Case Material:
Plastic
End Application:
Type no. Rtc-2
Mounting Configuration:
Four 0.112 in. Diameter mtg holes on 2.250 in. Mtg centers
Voltage Rating:
60.0 volts
Scale Measurement Range:
-2.5/+2.5
Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Main Contact Current Type:
Dc
Main Contact Current Rating:
0.006 amperes
Meter Movement Current Type:
Dc
Meter Movement Voltage In Volts:
0.100
Meter Movement Current Range:
+0.0/+100.0 microamperes
Meter Mounting Type:
Flush
Contact Closing Condition:
Increase value
Reset Facility Feature:
Provided
Lock In Device Type:
Coil
Release Method:
Deenergize lock-in coil
Meter Depth Behind Mounting Flange:
2.015 inches
Mounting Flange Diameter:
3.000 inches
Meter Body Diameter:

2.750 inches

## NSN 5945-00-226-0131

Meter Movement Relay - Page 2 of 2



S	рe	cial	Fe	atι	ire	s:
---	----	------	----	-----	-----	----

135 cps error -- fs equals 100 uadc marked on meter face

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T142-k