NSN 5945-00-226-1081

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-226-1081

| Thread Class: | |
|---|---|
| 2a single mounting facility | |
| Overall Length: | |
| 1.780 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | : |
| 1.406 inches single mounting facility | |
| Overall Height: | |
| 1.120 inches | |
| Overall Width: | |
| 1.650 inches | |
| Environmental Protection: | |
| Hermetic | |
| Winding Quantity: | |
| 1 | |
| Coil Quantity: | |
| 1 | |
| Winding Dc Resistance Rating: | |
| 1.0 kilohms single winding | |
| Duty Type: | |
| Intermittent | |
| Mounting Facility Type And Quantity: | |
| 2 threaded stud single mounting facility | |
| Features Provided: | |
| Polarized | |
| Thread Size: | |
| 0.138 inches single mounting facility | |
| Mounting Facility Pattern: | |
| In-line single mounting facility | |
| Operating Current Rating And Type: | |
| 9.0 milliamperes dc single winding | |
| Time Delay: | |
| 0.010 seconds fixed operate time | |
| Main Contact Load Current Rating At Maximum Rated Voltage: | |
| 2.0 amperes ac resistive load and 5.0 amperes dc resistive load | |
| Main Contact Maximum Voltage Rating In Volts: | |
| 115.0 ac and 29.0 dc | |
| Thread Series Designator: | |
| Unc single mounting facility | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

--

NSN 5945-00-226-1081

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300