NSN 5945-00-229-2682

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-229-2682

Thread Class: 2a single mounting facility Overall Length: 2.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.687 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
Overall Length: 2.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.687 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
2.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.687 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.687 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
2.687 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
Overall Height: 3.000 inches Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
3.000 inches Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
Overall Width: 2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
2.250 inches End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
End Application: General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
General application electronics (gen-ap-e) Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
Frequency In Hertz: 60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
60.0 Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent
1 Coil Quantity: 1 Duty Type: Intermittent
Coil Quantity: 1 Duty Type: Intermittent
1 Duty Type: Intermittent
Duty Type: Intermittent
Intermittent
Mounting Facility Type And Quantity:
2 threaded stud single mounting facility
Thread Size:
0.164 inches single mounting facility
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
300.0 ac
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
2 screw energizing element
Shelf Life:
N/a
Unit Of Measure:

NSN 5945-00-229-2682

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300