

View Online at <https://aerobasegroup.com/nsn/5945-00-230-2055>

**Thread Class:**

2b single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

2.875 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

1.687 inches

**Overall Width:**

1.812 inches

**Case Material:**

Metal

**Environmental Protection:**

Dustproof

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

130.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 threaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

8.788 cubic inches

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

28.0 ac

**Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

12.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

12.0 amperes ac resistive load

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

10 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300