

View Online at <https://aerobasegroup.com/nsn/5945-00-230-2055>

Thread Class:

2b single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

2.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.687 inches

Overall Width:

1.812 inches

Case Material:

Metal

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

130.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 threaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

8.788 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300