

View Online at <https://aerobasegroup.com/nsn/5945-00-231-3870>

Overall Length:

1.400 inches

Overall Height:

1.365 inches

Overall Width:

0.430 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold flash

End Application:

Central office, telephone auto; austin ship class lpd-4 amphibious transport docks, whidbey island class lsd, spruance class dd (963), general purpose electronic test equipment gpete, airborne mobile dir air spt ctl (21d), (02m jul83) (an/uyq-3a); landing craft air cushion (lcac); radar set, lightweight 3d (an/tps-59); generator set, tact quiet, 10kw, 400hz, mep-813a; radar set, firefinder (an/tpq-36)

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

800.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 terminal single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.822 cubic inches

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

7.5 amperes ac resistive load and 7.5 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Energizing Element Power Rating:

1.6 watts

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

14 tab, solder lug energizing element and contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300