## NSN 5945-00-232-1809

Electrical Solenoid - Page 1 of 2

**Thread Class:** 

2a mounting facility stud



View Online at https://aerobasegroup.com/nsn/5945-00-232-1809

Body Style:
Base end actuator
Bolt Circle Diameter:
1.250 inches
Body Diameter:
1.950 inches
Body Height:
1.158 inches
Case Material:
Any acceptable
Case Surface Treatment:
Any acceptable
Environmental Protection:
Humidity proof
Actuator Length:
0.562 inches
Actuator Diameter:
0.249 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
Magnetic Coil Quantity:
1
1 Duty Type:
1  Duty Type:  Continuous
1  Duty Type:  Continuous  Terminal Location:
1  Duty Type: Continuous  Terminal Location: Circumference
1  Duty Type: Continuous  Terminal Location: Circumference Voltage Rating In Volts:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi):
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi): 32 mounting facility stud
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi): 32 mounting facility stud Actuator Stroke Type:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi): 32 mounting facility stud Actuator Stroke Type: Rotary
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi): 32 mounting facility stud Actuator Stroke Type: Rotary Power Takeoff Connection Type:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi): 32 mounting facility stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Plain
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi): 32 mounting facility stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Plain Thread Size:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Thready Qty Per Inch (tpi): 32 mounting facility stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Plain Thread Size: 0.164 inches mounting facility stud

## NSN 5945-00-232-1809

Electrical Solenoid - Page 2 of 2

**Fiig:** A134a0



Rotation Direction And Energizing Stroke In Angular Deg:
40.0 clockwise
Thread Series Designator:
Unc mounting facility stud
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No