NSN 5945-00-232-2365

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-232-2365

2.030 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.375 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.375 inches single mounting facility Overall Height: 2.370 inches Overall Width: 1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes do single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts do 25 degrees celsius single winding and 32.0 volts do 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes do resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Overall Length:
1.375 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.375 inches single mounting facility Overall Height: 2.370 inches Overall Width: 1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes do single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes do resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	2.030 inches
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.375 inches single mounting facility Overall Height: 2.370 inches Overall Width: 1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Center To Center Distance Between Mounting Facilities Parallel To Length:
1.375 inches single mounting facility Overall Height: 2.370 inches Overall Width: 1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Type And Quantity: 9 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes do single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts do 25 degrees celsius single winding and 32.0 volts do 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes do resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	1.375 inches single mounting facility
Overall Height: 2.370 inches Overall Width: 1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Type And Quantity: 9 unthreaded hole single mounting facility Operating Current Rating And Type: 0.16 amperes do single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts do 25 degrees celsius single winding and 32.0 volts do 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes do resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Center To Center Distance Between Mounting Facilities Parallel To Width:
2.370 inches Overall Width: 1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	1.375 inches single mounting facility
Overall Width: 1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Overall Height:
1.680 inches Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	2.370 inches
Unthreaded Mounting Hole Diameter: 0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Overall Width:
0.152 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	1.680 inches
Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Unthreaded Mounting Hole Diameter:
Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	0.152 inches single mounting facility
Coil Quantity: 1 Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Winding Quantity:
Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	1
Winding Dc Resistance Rating: 162.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Coil Quantity:
Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	1
Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Winding Dc Resistance Rating:
Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	162.0 ohms single winding
Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Duty Type:
4 unthreaded hole single mounting facility Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Continuous
Mounting Facility Pattern: Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Mounting Facility Type And Quantity:
Rectangular single mounting facility Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	4 unthreaded hole single mounting facility
Operating Current Rating And Type: 0.16 amperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Mounting Facility Pattern:
Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Rectangular single mounting facility
Operating Voltage Rating And Type At Specificationified Temp: 16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Operating Current Rating And Type:
16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	0.16 amperes dc single winding
Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Operating Voltage Rating And Type At Specificationified Temp:
12.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	16.0 volts dc 25 degrees celsius single winding and 32.0 volts dc 25 degrees celsius single winding
Main Contact Maximum Voltage Rating In Volts: 24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	Main Contact Load Current Rating At Maximum Rated Voltage:
24.0 dc Shelf Life: N/a Unit Of Measure: Demilitarization:	12.0 amperes dc resistive load
Shelf Life: N/a Unit Of Measure: Demilitarization:	Main Contact Maximum Voltage Rating In Volts:
N/a Unit Of Measure: Demilitarization:	24.0 dc
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Fiig:	NO .
A03300	Fiig: