NSN 5945-00-235-3211

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-235-3211 |
|---|
| Overall Length: |
| 0.898 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.697 inches single mounting facility |
| Overall Height: |
| 1.200 inches |
| Overall Width: |
| 0.654 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Dustproof |
| Unthreaded Mounting Hole Diameter: |
| 0.198 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 0.704 cubic inches |

Mounting Facility Pattern:

In-line single mounting facility Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

NSN 5945-00-235-3211

Electromagnetic Relay - Page 2 of 2



| Main Contact Maximun | Voltage Rating In Volts: |
|----------------------|--------------------------|
|----------------------|--------------------------|

120.0 ac

Terminal Type And Quantity:

6 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300