# NSN 5945-00-235-5236

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-235-5236

# Thread Class:

2b single mounting facility

## **Overall Length:**

2.620 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility

## **Overall Height:**

4.620 inches

## **Overall Width:**

2.560 inches

**Environmental Protection:** 

Dustproof

#### Frequency In Hertz:

## Between 50.0 and 60.0

Winding Quantity:

1

#### Coil Quantity:

1

Winding Dc Resistance Rating:

332.0 ohms single winding

#### Duty Type:

Continuous

## Mounting Facility Type And Quantity:

4 threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.164 inches single mounting facility

#### Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

## **Operating Current Rating And Type:**

1.20 amperes ac single winding

## Time Delay:

1.00 seconds adjustable operate time and 900.00 seconds adjustable operate time

## Operating Voltage Rating And Type At Specificationified Temp:

230.0 volts ac 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

NSN 5945-00-235-5236

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

550.0 ac and 220.0 dc

**Thread Series Designator:** 

Unc single mounting facility

Terminal Type And Quantity:

4 pin all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300