NSN 5945-00-235-8511

Electromagnetic Relay - Page 1 of 2

Overall Length: 2.906 inches



View Online at https://aerobasegroup.com/nsn/5945-00-235-8511

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility
Overall Height:
1.406 inches
Overall Width:
1.531 inches
Mounting Slot Width:
0.156 inches single mounting facility
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
Purpose For Which Designed: General
General
General Coil Quantity:
General Coil Quantity: 1
General Coil Quantity: 1 Winding Dc Resistance Rating:
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type:
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method:
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 slotted hole single mounting facility
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type:
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type: General purpose warehouse
Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type: General purpose warehouse Cubic Measure:
General Coil Quantity: 1 Winding Dc Resistance Rating: 32.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 6.255 cubic inches

2 pole, double throw, one position momentary

NSN 5945-00-235-8511

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load and 12.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

8 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300