# NSN 5945-00-235-8952

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-00-235-8952

0.610 inches
Overall Height:
0.320 inches
Overall Width:
0.310 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.2 kilohms single winding and 1.5 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.060 cubic inches

0.004 seconds fixed operate and release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

### Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5945-00-235-8952

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quanti	ty	:
--------------------------	----	---

8 wire lead all functions

**Specification Data:** 

81349-mil-r-5757/37 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300