NSN 5945-00-236-1432

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-236-1432

Thread Class:

2a single mounting facility

Overall Length:

1.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.250 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.438 inches single mounting facility

Overall Height:

2.310 inches

Overall Width:

0.870 inches

Environmental Protection:

Salt spray resistant and salt water resistant

Frequency In Hertz:

60.0

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

159.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

160.0 milliamperes ac single winding

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

110.0 ac and 20.0 dc

NSN 5945-00-236-1432

Electromagnetic Relay - Page 2 of 2



Special	Features
Resistar	nt to salt w

vater spray **Thread Series Designator:**

Unc single mounting facility

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300