NSN 5945-00-236-7012

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-236-7012

Overall Length:
3.700 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.250 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.687 inches single mounting facility
Overall Height:
3.200 inches
Overall Width:
3.303 inches
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.218 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, momentary action
Operating Current Rating And Type:
600.0 milliamperes dc single winding
Time Delay:
0.06 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
25.0 amperes ac resistive load and 25.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
440.0 ac and 28.0 dc
Terminal Type And Quantity:
8 pin all functions
Shelf Life:
N/a
Unit Of Measure:

NSN 5945-00-236-7012

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300