NSN 5945-00-237-1237

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-237-1237
Overall Length:
2.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.062 inches single mounting facility
Overall Height:
2.437 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.156 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.500 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Type a-s-ac, b-s-ac, c-s-ac and d-s-ac
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Pile-up Main Contact Form Arrangement:
1b and 1b
Storage Type:
General purpose warehouse
Cubic Measure:
13.404 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Operating Current Rating And Type:

260.0 milliamperes ac single winding

NSN 5945-00-237-1237

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

70.0 milliamperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300