NSN 5945-00-237-1237

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-237-1237

Overall Length: 2.750 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.062 inches single mounting facility **Overall Height:** 2.437 inches **Overall Width:** 2.000 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Height: 1.500 inches single mounting facility **Fragility Factor:** Moderately rugged **End Application:** Type a-s-ac, b-s-ac, c-s-ac and d-s-ac **Frequency In Hertz:** 60.0 Winding Quantity: 1 Purpose For Which Designed: General **Coil Quantity:** 1 Winding Dc Resistance Rating: 1.0 ohms single winding **Duty Type:** Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility **Pile-up Main Contact Form Arrangement:** 1b and 1b Storage Type: General purpose warehouse **Cubic Measure:** 13.404 cubic inches **Mounting Facility Pattern:** Rectangular single mounting facility **Operating Current Rating And Type:** 260.0 milliamperes ac single winding

NSN 5945-00-237-1237

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

70.0 milliamperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300