NSN 5945-00-237-1283

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-237-1283

Overall Length:

9.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility

Overall Height:

5.000 inches

Overall Width:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.344 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

5.3 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

0.3 amperes ac single winding

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 25.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac and 300.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load

NSN 5945-00-237-1283

Electromagnetic Relay - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

10 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300