NSN 5945-00-237-3206

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-237-3206

| Thread Class: |
|--|
| 2b single mounting facility |
| Overall Length: |
| 4.620 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility |
| Overall Height: |
| 2.310 inches |
| Overall Width: |
| 3.250 inches |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 140.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded hole single mounting facility |
| Thread Size: |
| 0.216 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 5 pole, double throw, one position momentary |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.812 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 120.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 10.0 amperes ac resistive load and 10.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 24.0 dc |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5945-00-237-3206

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300