## NSN 5945-00-238-9786

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-238-9786

**Thread Class:** 

2a single mounting facility

**Overall Length:** 

1.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

**Overall Height:** 

1.870 inches

Overall Width:

1.400 inches

**Environmental Protection:** 

Humidity resistant and salt water resistant

Winding Quantity:

1

**Coil Quantity:** 

Winding Dc Resistance Rating:

70.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 clinch nut single mounting facility

**Thread Size:** 

0.138 inches single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

**Operating Current Rating And Type:** 

140.0 milliamperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp:

13.2 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

110.0 ac and 24.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

## NSN 5945-00-238-9786

Electromagnetic Relay - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A03300