## NSN 5945-00-239-2411

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-239-2411

## **Overall Length:**

2.680 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

#### **Overall Height:**

1.500 inches

#### **Overall Width:**

1.620 inches

#### **Environmental Protection:**

Fungus proof

#### **Unthreaded Mounting Hole Diameter:**

0.156 inches single mounting facility

#### Winding Quantity:

1

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

44.0 ohms single winding

## **Duty Type:**

Continuous

#### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

## **Mounting Facility Pattern:**

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### **Nonpile-up Auxiliary Contact Arrangement:**

1 pole, double throw, one position momentary

## **Auxiliary Contact Maximum Voltage Rating In Volts:**

115.0 ac and 32.0 dc

## Operating Voltage Rating And Type At Specificationified Temp:

8.3 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

 $5.0 \ \text{amperes}$  ac resistive load and  $2.5 \ \text{amperes}$  dc resistive load

## **Main Contact Maximum Voltage Rating In Volts:**

460.0 ac and 32.0 dc

## **Special Features:**

Tropicalized

## **Terminal Type And Quantity:**

11 pin all functions

# NSN 5945-00-239-2411

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300