NSN 5945-00-250-5616

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-250-5616

Thread Class:

2b single mounting facility

Overall Length:

2.870 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.560 inches

Overall Width:

1.810 inches

Environmental Protection:

Salt spray resistant

Winding Quantity:

,

Coil Quantity:

Winding Dc Resistance Rating:

40.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

200.0 milliamperes dc single winding

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

7.0 amperes ac resistive load

NSN 5945-00-250-5616

Electromagnetic Relay - Page 2 of 2

Fiig: A03300



Main Contact Maximum Voltage Rating In Volts: 115.0 ac Auxiliary Contact Load Current Rating At Maximum Rated Voltage: 13.0 amperes ac resistive load Special Features: Resistant to salt water spray Thread Series Designator: Unc single mounting facility Terminal Type And Quantity: 10 pin all functions Shelf Life: N/a Unit Of Measure: -- Demilitarization: No