

View Online at <https://aerobasegroup.com/nsn/5945-00-253-7175>

Overall Length:

1.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.400 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.300 inches single mounting facility

Overall Height:

0.950 inches

Overall Width:

0.730 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.096 inches single mounting facility

Contact Material:

Silver

Contact Surface Treatment:

Gold

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

1.6 kilohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.005 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

40.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Energizing Element Power Rating:

1.0 watts

Precious Material And Location:

Contact surfaces gold and contacts silver

Precious Material:

Gold and silver

Terminal Type And Quantity:

16 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300