## NSN 5945-00-256-0670

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-256-0670

Overall Length:
4.520 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.750 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.880 inches single mounting facility
Overall Height:
3.090 inches
Overall Width:
3.250 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
45.392 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:

1.00 minutes adjustable release time and 10.00 minutes adjustable release time

## NSN 5945-00-256-0670

Electromagnetic Relay - Page 2 of 2



## **Operating Voltage Rating And Type At Specificationified Temp:**

440.0 volts ac 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

480.0 ac and 110.0 dc

**Terminal Type And Quantity:** 

8 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300