## NSN 5945-00-257-0578

Electromagnetic Relay - Page 1 of 2

**Thread Class:** 

2b single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-257-0578

Thread Direction:
Right-hand single mounting facility
Overall Length:
1.000 inches
Overall Height:
1.848 inches
Overall Width:
0.980 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
Coil Quantity:
-
1
1 Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 650.0 ohms single winding
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility Storage Type:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility Storage Type: General purpose warehouse
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 1.811 cubic inches
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 1.811 cubic inches Thready Qty Per Inch (tpi):
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 1.811 cubic inches Thready Qty Per Inch (tpi): 32 single mounting facility
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 1.811 cubic inches Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size:

## NSN 5945-00-257-0578

Electromagnetic Relay - Page 2 of 2



Time Delay:
0.013 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
24.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
3.0 amperes ac resistive load and 3.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
240.0 ac and 32.0 dc
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
8 tab, solder lug all functions
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No

**Fiig:** A03300