## NSN 5945-00-257-6970

Electromagnetic Relay - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

2a single mounting facility

Right-hand single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-257-6970

| Overall Length:  |
|--|
| 1.625 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.938 inches single mounting facility                                    |
| Overall Height:  |
| 2.437 inches   |
| Overall Width:   |
| 1.406 inches   |
| Case Material:   |
| Metal  |
| Environmental Protection:  |
| Hermetic   |
| Fragility Factor:  |
| Moderately rugged  |
| Contact Material:  |
| Silver   |
| Winding Quantity:  |
| 1  |
| Purpose For Which Designed:  |
| General  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 100.0 ohms single winding  |
| Duty Type:   |
| Continuous   |
| Arc Quenching Method:  |
| Air  |
| Mounting Facility Type And Quantity:                                     |
| 3 threaded stud single mounting facility                                 |
| Storage Type:  |
| General purpose warehouse  |
| Cubic Measure:   |
| 5.567 cubic inches   |
| Thready Qty Per Inch (tpi):  |
| 32 single mounting facility  |
| Thread Size:   |

0.138 inches single mounting facility

## NSN 5945-00-257-6970

Electromagnetic Relay - Page 2 of 2

**Fiig:** A03300



| Mounting Facility Pattern:   |
|--|
| Triangle single mounting facility  |
| Nonpile-up Main Contact Arrangement:   |
| 2 pole, double throw, one position momentary   |
| Time Delay:  |
| 0.025 seconds fixed operate time   |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.188 inches single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 12.0 volts dc 25 degrees celsius single winding  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |
| 3.0 amperes ac resistive load and 3.0 amperes dc resistive load  |
| Main Contact Maximum Voltage Rating In Volts:  |
| 115.0 ac and 26.5 dc   |
| Precious Material And Location:  |
| Contacts silver  |
| Precious Material:   |
| Silver   |
| Thread Series Designator:  |
| Unc single mounting facility   |
| Terminal Type And Quantity:  |
| 8 wire hook all functions  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |