NSN 5945-00-257-7227

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-257-7227 |
|--|
| Overall Length: |
| 3.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.500 inches single mounting facility |
| Overall Height: |
| 3.120 inches |
| Overall Width: |
| 2.500 inches |
| Environmental Protection: |
| Dustproof |
| Unthreaded Mounting Hole Diameter: |
| 0.196 inches single mounting facility |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 121.0 ohms all windings |
| Duty Type: |
| Intermittent |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 two circuit, two positions momentary |
| Operating Current Rating And Type: |
| 760.0 milliamperes dc all windings |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 22.0 volts dc 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 3.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Special Features: |
| Constant voltage coil is supplied w/approx 22v, variable voltage coil is supplied w/a variable voltage from generator, relay operates when |
| voltage on variable voltage coil drops below 15v approx |
| Terminal Type And Quantity: |
| 6 pin all functions |

N/a

Shelf Life:

NSN 5945-00-257-7227

Electromagnetic Relay - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A03300