NSN 5945-00-257-9071

Electromagnetic Relay - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5945-00-257-9071

| Overall Length: |
|--|
| 9.625 inches |
| Overall Height: |
| 6.000 inches |
| Overall Width: |
| 3.250 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.312 inches single mounting facility |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 76.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole single mounting facility |
| Features Provided: |
| Latching contacts |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 6 pole, single throw, normally open, momentary action |
| Operating Current Rating And Type: |
| 1.80 amperes ac single winding |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 7.750 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 440.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 12.7 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 440.0 ac |
| Special Features: |
| A. 2 of the 6 poles connected in series by a removable connecting bar |
| Terminal Type And Quantity: |
| 14 pin all functions |
| Shelf Life: |

NSN 5945-00-257-9071

Electromagnetic Relay - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A03300