NSN 5945-00-257-9467

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-257-9467

Overall Length:
0.810 inches
Overall Height:
0.612 inches
Overall Width:
0.410 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
66.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Orange Total
Storage Type:
General purpose warehouse
General purpose warehouse
General purpose warehouse Cubic Measure:
General purpose warehouse Cubic Measure: 0.203 cubic inches
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement:
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay:
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate and release time
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp:
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 6.0 volts dc 25 degrees celsius single winding
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 6.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 6.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load
General purpose warehouse Cubic Measure: 0.203 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 6.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

8 pin all functions

Terminal Type And Quantity:

NSN 5945-00-257-9467

Electromagnetic Relay - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-r-5757/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300