NSN 5945-00-258-0309

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-258-0309

Thread Class: 2a single mounting facility **Thread Length:** 0.375 inches single mounting facility **Overall Length:** 1.620 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.933 inches single mounting facility and 0.943 inches single mounting facility **Overall Height:** 2.060 inches **Overall Width:** 1.430 inches **Environmental Protection:** Hermetic **End Application:** Type an/spq-5 Frequency In Hertz: 60.0 **Winding Quantity: Coil Quantity:** Winding Dc Resistance Rating: 427.5 ohms single winding and 522.5 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 3 threaded stud single mounting facility **Thread Size:** 0.138 inches single mounting facility **Mounting Facility Pattern:** Triangle single mounting facility **Operating Current Rating And Type:** 242.0 milliamperes ac single winding **Operating Voltage Rating And Type At Specificationified Temp:** 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 3.0 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 115.0 ac and 27.5 dc **Special Features:** 2nd c to c distance between mtg studs 1.187 in. Plus 0.005

NSN 5945-00-258-0309

Electromagnetic Relay - Page 2 of 2



Ī	hread	Series	Desig	nator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300