NSN 5945-00-258-1634

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-258-1634

| Thread Class: |
|---|
| 2a single mounting facility |
| Overall Length: |
| 1.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.500 inches single mounting facility |
| Overall Height: |
| 2.120 inches |
| Overall Width: |
| 1.000 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 100.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Inert gas |
| Mounting Facility Type And Quantity: |
| 2 threaded stud single mounting facility |
| Thread Size: |
| 0.112 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Operating Current Rating And Type: |
| 18.0 milliamperes dc all windings and 20.0 milliamperes dc all windings |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 18.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5945-00-258-1634

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300