NSN 5945-00-258-2626

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-258-2626

Thread Class:

2a mounting facility stud

Thread Direction:

Right-hand mounting facility stud

Body Style:

Double ended actuator

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.719 inches

Body Diameter:

1.156 inches

Body Height:

0.640 inches

Case Material:

Steel

Case Surface Treatment:

Cadmium and chromium

Fragility Factor:

Moderately rugged

Inclosure Type:

Fully enclosed

Magnetic Coil Quantity:

1

Electrical Resistance:

100.70 ohms

Duty Type:

Continuous

Terminal Location:

Circumference

Voltage Rating In Volts:

28.0 dc

Mounting Facility Type And Quantity:

2 threaded stud

Current Rating:

3.0 amperes

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

48 mounting facility stud

Actuator Stroke Type:

Rotary

Power Takeoff Connection Type:

Plate coupling

NSN 5945-00-258-2626

Electrical Solenoid - Page 2 of 2



Plate Coupling Facility And Quantity: 1 unthreaded hole Plate Coupling Facility Diameter: 0.875 inches Plate Coupling Facility Radius: 0.437 inches **Thread Size:** 0.099 inches mounting facility stud **Mounting Facility Pattern:** Two position in-line **Rotation Direction And Energizing Stroke In Angular Deg:** 25.0 clockwise **Thread Series Designator:** Unc mounting facility stud **Terminal Type And Quantity:** 2 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A134a0