NSN 5945-00-258-3463

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-258-3463

Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Thread Class: 2a single mounting facility **Overall Length:** 1.546 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.000 inches single mounting facility **Overall Height:** 2.375 inches **Overall Width:** 1.343 inches **Environmental Protection:** Hermetic **End Application:** Type no. An/aps-42 Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 200.0 ohms single winding **Duty Type:** Continuous **Arc Quenching Method:** Inert gas **Mounting Facility Type And Quantity:** 3 threaded stud single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility **Mounting Facility Pattern:** Triangle single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, single throw, normally open, momentary action **Operating Current Rating And Type:** 80.0 milliamperes dc single winding Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.200 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding

NSN 5945-00-258-3463

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 24.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

6 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300