

View Online at <https://aerobasegroup.com/nsn/5945-00-258-7800>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.328 inches single mounting facility

Overall Length:

3.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.813 inches single mounting facility

Overall Height:

2.500 inches

Overall Width:

1.750 inches

Case Material:

Brass

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

2

Winding Dc Resistance Rating:

2.5 kilohms all windings

Duty Type:

Continuous

Arc Quenching Method:

Inert gas

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

16.669 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, single throw, normally open, momentary action

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.594 inches single mounting facility

Minimum Differential Electrical Operating Rating:

4.2 milliamperes

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Special Features:

A. When the current difference reaches 0.0042 amp in two coils the coil with the higher current will close two sets of spst, normally open contacts, when the same current difference appears in other coil the other two sets of spst normally open contacts will close, and the first set of contacts will open

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

12 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300