## NSN 5945-00-258-7800

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-258-7800

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Thread Length:
0.328 inches single mounting facility
Overall Length:
3.810 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.813 inches single mounting facility
Overall Height:
2.500 inches
Overall Width:
1.750 inches
Case Material:
Brass
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Winding Dc Resistance Rating:
2.5 kilohms all windings
Duty Type:
Continuous
Arc Quenching Method:
Inert gas
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Storage Type:

Polarized

**Cubic Measure:** 

16.669 cubic inches

**Features Provided:** 

General purpose warehouse

## NSN 5945-00-258-7800

Electromagnetic Relay - Page 2 of 2



Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.164 inches single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, single throw, normally open, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
2.594 inches single mounting facility
Minimum Differential Electrical Operating Rating:
4.2 milliamperes
Main Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes ac resistive load and 5.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Special Features:
A. When the current difference reaches 0.0042 amp in two coils the coil with the higher current will close two sets of spst, normally open
contacts, when the same current difference appears in other coil the other two sets of spst normally open contacts will close, and the first set
of contacts will open
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
12 tab, solder lug all functions
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A03300