## NSN 5945-00-259-1892

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-259-1892

| Thread Class:  |
|--|
| 2a single mounting facility  |
| Overall Length:  |
| 1.620 inches   |
| Overall Height:  |
| 2.060 inches   |
| Overall Width:   |
| 1.430 inches   |
| Environmental Protection:  |
| Hermetic   |
| Winding Quantity:  |
| 1  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 350.0 ohms single winding  |
| Duty Type:   |
| Continuous   |
| Mounting Facility Type And Quantity:   |
| 3 threaded stud single mounting facility   |
| Thready Qty Per Inch (tpi):  |
| 32 single mounting facility  |
| Thread Size:   |
| 0.138 inches single mounting facility  |
| Mounting Facility Pattern:   |
| Triangle single mounting facility  |
| Nonpile-up Main Contact Arrangement:   |
| 3 pole, double throw, one position momentary   |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.188 inches single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 26.5 volts dc 25 degrees celsius single winding  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |
| 6.0 amperes ac resistive load and 2.0 amperes dc resistive load  |
| Main Contact Maximum Voltage Rating In Volts:  |
| 115.0 ac and 24.0 dc   |
| Thread Series Designator:  |
| Unc single mounting facility   |
| Terminal Type And Quantity:  |
| 11 pin all functions   |
| Shelf Life:  |

N/a

## NSN 5945-00-259-1892

Electromagnetic Relay - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A03300