## NSN 5945-00-259-1896

Electrical Solenoid - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5945-00-259-1896

2a mounting facility stud
Body Style:
Base end actuator
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.250 inches
Body Diameter:
1.750 inches
Body Height:
1.000 inches
Case Material:
Steel
Case Surface Treatment:
Cadmium
Environmental Protection:
Any acceptable
Actuator Diameter:
0.250 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
1
Electrical Resistance:
117.30 ohms
Duty Type:
Continuous
Terminal Location:
Circumference
Voltage Rating In Volts:
90.0 dc
Mounting Facility Type And Quantity:
2 threaded stud
Current Rating:
767.0 milliamperes
Torque Rating And Type:
1.20 inch-pounds starting and 1.80 inch-pounds end
Thready Qty Per Inch (tpi):
32 mounting facility stud
Actuator Stroke Type:
Rotary
Power Takeoff Connection Type:
Press fitted onto a cam

## NSN 5945-00-259-1896

Electrical Solenoid - Page 2 of 2

A134a0



Thread Size:
0.164 inches mounting facility stud
Mounting Facility Pattern:
Two position in-line
Rotation Direction And Energizing Stroke In Angular Deg:
45.0 counterclockwise
Special Features:
One wire lead 7.500 in. Lg with terminal, one wire lead 4.500 in. Lg with terminal lug $$
Thread Series Designator:
Unc mounting facility stud
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: