NSN 5945-00-259-2169



| Electromagnetic Relay - Page 1 of 2 | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/5945-00-259-2169 | |
| Thread Class: | |
| 2b single mounting facility | |
| Overall Length: | |
| 5.438 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 4.375 inches single mounting facility | |
| Overall Height: | |
| 2.812 inches | |
| Overall Width: | |
| 2.500 inches | |
| Environmental Protection: | |
| Dustproof and fungus proof | |
| Frequency In Hertz: | |
| 60.0 | |
| Winding Quantity: | |
| | |

Coil Quantity:

Duty Type:

Intermittent

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 threaded hole single mounting facility

Features Provided:

Latching contacts

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.190 inches single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Operating Current Rating And Type:

4.0 amperes ac single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 300.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Special Features:

Pushbutton reset included

NSN 5945-00-259-2169

Electromagnetic Relay - Page 2 of 2



| Thread | Series | Design | ator |
|--------|---------------|--------|------|
| | | | |

Unc single mounting facility

Terminal Type And Quantity:

6 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300