## NSN 5945-00-259-2211

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-259-2211 **Thread Class:** 2a single mounting facility **Overall Length:** 1.780 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.218 inches single mounting facility **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.218 inches single mounting facility **Overall Height:** 2.250 inches **Overall Width:** 1.656 inches **Environmental Protection:** Hermetic **End Application:** Type no. An/urn13 Frequency In Hertz: 60.0 **Winding Quantity: Coil Quantity:** Winding Dc Resistance Rating: 26.0 ohms single winding **Duty Type:** Continuous **Arc Quenching Method: Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility **Pile-up Main Contact Form Arrangement:** Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility **Operating Current Rating And Type:** 46.0 milliamperes ac single winding Operating Voltage Rating And Type At Specificationified Temp:

132.0 volts ac 25 degrees celsius single winding

## NSN 5945-00-259-2211

Electromagnetic Relay - Page 2 of 2



Main	Contact	I oad (	Current	Rating	Δt	Maximum	Rated	Voltage:
viaiii	Contact	LUau v	Julient	Naumu	$\Delta \iota$	IVIANIIIIUIII	Nateu	VUILAUE.

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

\_\_

Demilitarization:

No

Fiig:

A03300