NSN 5945-00-259-6058

Electrical Solenoid - Page 1 of 2

200.0 milliamperes



View Online at https://aerobasegroup.com/nsn/5945-00-259-6058

Thread Class:
2a mounting facility stud
Thread Direction:
Right-hand mounting facility stud
Body Style:
Base end actuator
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Body Diameter:
1.140 inches
Body Height:
0.641 inches
Case Material:
Steel
Case Surface Treatment:
Cadmium
Environmental Protection:
Any acceptable
Maximum Operating Temp:
65.0 degrees celsius
Actuator Length:
0.500 inches
Fragility Factor:
Moderately rugged
Actuator Diameter:
0.156 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
1
Electrical Resistance:
148.10 ohms
Duty Type:
Continuous
Terminal Location:
Circumference
Voltage Rating In Volts:
30.0 dc
Mounting Facility Type And Quantity:
2 threaded stud
Current Rating:

NSN 5945-00-259-6058 Electrical Solenoid - Page 2 of 2



Storage Type:
General purpose warehouse
Torque Rating And Type:
0.40 inch-pounds starting and 2.20 inch-pounds end
Cubic Measure:
0.654 cubic inches
Thready Qty Per Inch (tpi):
48 mounting facility stud
Actuator Stroke Type:
Rotary
Power Takeoff Connection Type:
Plain
Thread Size:
0.099 inches mounting facility stud
Mounting Facility Pattern:
Two position in-line
Rotation Direction And Energizing Stroke In Angular Deg:
25.0 counterclockwise
Thread Series Designator:
Unc mounting facility stud
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A134a0