NSN 5945-00-259-6419

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-259-6419

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

1.344 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

Overall Height:

1.921 inches

Overall Width:

0.953 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

280.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

2.460 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

NSN 5945-00-259-6419

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, double throw, one position momentary
Time Delay:
0.015 seconds fixed operate time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.000 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
27.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
3.0 amperes ac resistive load and 3.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 26.5 dc
Precious Material And Location:
Contacts silver
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
11 wire hook all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300