

View Online at <https://aerobasegroup.com/nsn/5945-00-269-2840>

Overall Length:

1.470 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.130 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.005 inches single mounting facility

Overall Height:

0.400 inches

Overall Width:

1.450 inches

Unthreaded Mounting Hole Diameter:

0.096 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

1.8 kilohms single winding and 2.2 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

9.0 milliamperes dc single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 750.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-5757/13 government specification

Specification Or Standard:

Ry4xx383l30 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300