## NSN 5945-00-271-3216

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-271-3216

## **Overall Length:** 1.718 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 0.625 inches single mounting facility **Overall Height:** 1.280 inches **Overall Width:** 0.937 inches Mounting Slot Width: 0.150 inches single mounting facility **Case Material:** Metal **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged **Frequency In Hertz:** 60.0 Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity: Duty Type:** Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type: General purpose warehouse **Features Provided:** Polarized **Cubic Measure:** 2.060 cubic inches **Mounting Facility Pattern:** Triangle single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary **Time Delay:**

0.01 seconds fixed operate and release time

1

1

## NSN 5945-00-271-3216

Electromagnetic Relay - Page 2 of 2



**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:** 1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300